





轧机压下推力圆锥滚子轴承

The rolling mill depresses the thrust tapered roller bearing



轴径 mm		外形尺寸 mm								代号	轴向载 负荷 kg
d	D	D ₁	T	T ₁	d ₁	R	M	M _{1rmin}	r _{min}		
100	100	98	37	32	87	250	M8	1.5	—	4397/100	-
120	120	118	45	38	105	300	M10	1.5	—	4397/120	1635
150	150	148	55	47	127	457	M12	1.6	—	4397/150	2325
150	150	148	55	47	127	550	M12	1.6	—	4397/150K	2325
150	150	148	48	-	127	228.6	M12	1.6	—	4297/150	2325
175	175	173	62	53	152	457	M12	1.6	—	4397/175	3223
175	175	173	62	53	152	550	M12	1.6	—	4397/175K	3223
175	175	173	53	-	152	228.6	M12	1.6	—	4297/175	3223
203	203	201	75.6	65	178	508	M12	1.6	—	4397/203	4500
203	203	201	76	65.4	170.8	508	M12	1.6	—	4397/203K	4500
203	203	201	85	65	170	250	M12	1.6	—	4397/203K1	4500
203	203	201	65	-	178	254	M12	1.6	—	4297/205/HC	4584
205	205	203	76	65	178	508	M12	1.6	—	4397/205/HC	4585
205	205	203	65	-	178	254	M20	1.6	—	4297/205/HC	4585
235	235	233	85	73	208	560	M20	2	—	4397/235	6028
235	235	233	73	-	208	280	M20	2	—	4297/235	-
265	265	263	95	81	229	609	M20	2.1	—	4397/265/HC	7753
265	265	263	81	-	229	304.8	M20	2.4	—	4297/265	-
320	320	318	112	95	280	762	M20	2.4	—	4397/320	11500
320	320	318	122.7	95	280	470	M20	2.4	—	4397/320K	11500
320	320	318	118.5	95	280	550	M20	2.4	—	4397/320K1	-
330	330	328	95	-	280	381	M20	-	2.4	4297/330K	11500
377	377	375	129	112	330	914	M24	-	2.4	4397/377	-
377	377	375	129	112	330	930	M24	-	2.4	4397/377K	16044
377	377	375	112	-	330	457.2	M24	-	2.4	4297/377	-
380	380	378	129	112	330	914.4	M24	M30	2.4	4397/380	-
380	380	378	112	-	330	457.2	M24	M30	2.4	4297/380	-
410	410	408	142	122	355	1060	M24	M30	3	4397/410	-
410	410	408	122	-	355	508	M24	M30	3	4297/410	-
440	440	438	152	130	380	1016	M24	M36	3	4397/440	-
440	440	438	130	-	380	508	M24	M36	3	4297/440	23330
495	495	492	172	146	432	1066.8	M24	M36	3	4397/495	-
495	495	492	146	-	432	558.8	M24	M36	3	4297/495	-
525	525	522	180	155	460	1270	M24	M36	3	4397/525	36202
525	525	522	155	-	460	635	M24	M36	3	4297/525	-
555	555	552	192	165	482	1270	M24	M36	3	4397/555	-
555	555	552	165	-	482	635	M24	M36	3	4297/555	-

580	580	577	165	-	510	710	M24	M42	3	4297/580	41560
581	581.025	578.663	193.777	168.275	508	1422.4	M24	M42	3.2	-	38984
610	610	607	205	178	533	1524	M30	M42	3	4397/610	-
610	610	607	178	-	-	762	M30	M42	3	4297/610	-
640	640	637	214.5	185	550	1520	M30	M42	3	4397/640/HC	48560
640	640	637	185	-	550	762	M30	M42	3	4297/640	49200
710	710	705	250	210	610	1600	M30	M42	4	4397/710	-
710	710	705	250	205	610	1400	M30	M42	4	4397/710K	62703
750	750	745	260	225	650	1600	M30	M42	4	4397/750/HA/A1	63900
800	800	795	270	245	700	1700	M30	M48	5	4937/800	-
900	900	896	280	236	750	1800	M36	M48	6	4937/900/HC	94000

质量 kg
-
3.3
6.3
6.3
5.7
9.6
9.7
8.5
16
16.2
17
10.2
16.2
14.3
23.7
-
33.9
-
58.9
62.1
-
51.4
-
94.7
-
-
-
-
-
-
137
-
-
266
-
-
-

300.6
338
-
-
454
418
-
647
747
-
1150